

DECLARATION OF PERFORMANCE

No. DP-20

1. Unique product identification:
 MILLED QUICKLIME EN 459-1 CL 70-Q (Rsv, Psv)
2. Prescribed uses:
 Preparation of mortars, manufacture of other construction products (bricks, concrete, concrete, etc.) and civil engineering applications (soil treatment, asphalt mixtures, etc.)
3. Manufacturer:
 SC Carmeuse Holding SRL
 Plant: Fieni, Str. Gării, Nr.2, 135100 Fieni, Jud. Dâmbovița, Tel./Fax: +4 0245 774700, +4 0245 774121
4. Performance Constant Verification System:
 System 2+
5. Harmonized standard:
 SR EN 459-1:2011
 Notified Organization: AEROQ SA – identification number 1840


6. Declared performance:

Main Characteristics	Declared Performance	Harmonized technical specifications
CaO + MgO, %	min. 70	SR EN 459-1:2011
Var liber - CaO av, %	min. 55	
MgO, %	max. 5	
CO ₂ , %	max. 25	
SO ₃ , %	max. 2	
Stability	Pass	
Fineness: - passing through 2 mm, %	100	
- passing through 0.2 mm, %	min. 95	
- passing through 0.09 mm, %	min. 85	
Reactivity	NPD	

The performance of the product identified above is in accordance with the declared performance set.
 This Performance Statement is issued in accordance with Regulation (EU) No 305/2011, on the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
 Quality Manager, Gabriel Virlan
 in the Fieni Plant
 on March 10, 2016



 1840
SC Carmeuse Holding SRL
Str. Carierei, Nr. 127 A, 500052 Braşov, România Plant: Fieni, Str. Gării, Nr.2, 135100 Fieni, Jud. Dâmbovița
07
1840-CPR-97/555/EC/0120-07
DP-20
EN 459-1
Milled Quicklime EN 459-1 CL 70-Q (Rsv, Psv)
Applications or building materials and civil engineering Declared performance per levels or classes is defined in the standard lime designation label