

## **Deadburnt Dolomite**

Revision date: July 11, 2019

#### 1. Identification

Product Name:	Deadburnt dolomite	
Synonyms:	Ferrodolime Fines, Ferrodolime ROK, Ferrodolime-Small,	Burnt Dolomite, Fusite,
Recommended Uses:	Water treatment, steel flux, construction	caustic agent, pH adjustment, acid gas absorption,
Manufacturer:	Carmeuse Americas	
	<u>US Office</u> 11 Stanwix Street, 21 <sup>st</sup> Floor Pittsburgh, PA 15222 Phone: (412) 995-5500 Fax: (412) 995-5594	<u>Canadian Office</u> PO Box 190 Ingersoll, ON N5C 3K5 Phone: (519) 423-6283 Fax: (519) 423-6545
Emergency Contact:	Infotrac: (800) 535-5053	(24 hrs a day, 7 days a week)

#### 2. Hazards Identification

GHS	Physical Hazard	ls	
classification	None		
	•	ation age	Category 2 Category 1 Category 1A Category 3 Category 1
GHS Label	Signal Word:	Danger	
Elements:	Hazard Statements:	Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause cancer through inhalation Causes damage to lungs through prolonged o inhalation.	or repeated exposure by
	Precautionary Statements:	Obtain special instructions before use. Do not handle until all safety precautions hav understood. Keep container tightly closed Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this pe Use only outdoors or in well-ventilated area Wear protective gloves, clothing and eye pro- Do not use water on material spills.	roduct.



## **Deadburnt Dolomite**

Revision date: July 11, 2019

### Pictograms:



### 3. Composition

<u>Chemical name</u>	<u>% by weight</u>	<u>CAS#</u>
Calcium oxide	> 55	1305-78-8
Magnesium oxide	< 34	1309-48-4
Iron Oxide	< 12	1309-37-1
Silica-crystalline quartz	0.1 - 2	14808-60-7

#### 4. First Aid Measures

Eyes:	Immediately flush eyes with generous amounts of water for at least 15 minutes. Pull back the eyelid to ensure that all lime dust has been washed out. Seek medical attention immediately. Do not rub eyes.
Skin:	Wash exposed area with large amounts of water. Seek medical attention immediately.
Ingestion:	Do not induce vomiting. Seek medical attention immediately. Never give anything by mouth unless instructed to do so by medical personnel.
Inhalation:	Move victim to fresh air. Seek medical attention if necessary. If breathing has stopped, give artificial respiration
Most Importa Symptoms:	<b>nt</b> Irritation of skin, eyes, gastrointestinal tract or respiratory tract.
Immediate me treatment?	edical attention / special See first aid information above. Note to Physicians: Provide general supportive measures and treat symptomatically.

#### 5. Fire Fighting Measures

Suitable (and unsuitable) fire extinguishing media:	Use dry chemical fire extinguisher. Do not use water or halogenated compounds, except that large amounts of water may be used to deluge small quantities of this product.
Specific hazards arising from the product	Inhalation, skin or eye contact, can result in serious injury. This product reacts with water, and can release heat sufficient to ignite combustible materials. This product is not considered to be an explosion hazard, although reaction with water or other incompatible materials may rupture containers. When this product is wet, it can be very slippery and can result in a slip hazard. Hazardous Combustion Products: None.



### **Deadburnt Dolomite**

Revision date: July 11, 2019

Special protective equipment and precautions for fire fighters Wear full fire-fighting turn-out gear (full Bunker gear), and respiratory protection (SCBA) to prevent inhalation, skin or eye contact.

#### 6. Accidental Release Measures

#### Personal precautions, protective equipment, emergency procedures:

Avoid inhalation, eye and skin contact. Avoid generating airborne dust. Wear appropriate protective clothing as described in section 8.

#### Methods and materials for containment and clean up:

Utilize cleanup methods that minimize generating dust: vacuum. Avoid dry sweeping. Do not use water on large spills, as this product reacts with water and releases heat. Residue on surfaces may be removed with copious amount of water or vinegar.

#### 7. Handling & Storage

Safe Handling:	Avoid inhalation, skin and eye contact. Avoid generating airborne dust. An eye wash station should be readily available when this product is handled.
Safe Storage:	Keep in tightly closed containers. Protect containers from physical damage. Store in a cool, dry, and well-ventilated location. Do not store near incompatible materials (see Section 10 below). Keep away from moisture. Long-term storage in aluminum containers is not recommended, as calcium oxide may corrode aluminum over long periods of time

#### 8. Exposure Controls/Personal Protection

Occupational Exposure Limits			
	OSHA PEL (mg/m³)	ACGIH TLV (mg/m <sup>3</sup> )	Ont. Reg. 833 TWAEV (mg/m³)
Calcium oxide	5	2	2
Magnesium oxide	15	10	10
Iron Oxide*	5 (fume) 15 (total) 5 (respirable)	5	5 (respirable)
Silica, crystalline quartz, cristobalite and tridymite	0.05 (respirable)	0.025 (respirable)	0.1

\*PELs for Particulates Not Otherwise Classified



# **Deadburnt Dolomite**

Revision date: July 11, 2019

Engineering Controls:	Use with adequate general or local exhaust ventilation and to maintain exposure below occupational exposure limits.
Individual Protection Measures (	Personal Protective Equipment):
Specific Eye / Face Protection:	Safety glasses with side shields. In windy conditions, or if work activity generates elevated airborne dust levels, dust proof or chemical goggles are recommended. Contact lenses should not be worn.
Specific Skin Protection:	When there is a risk of skin contact, wear appropriate clothing and gloves to prevent contact.
Specific Respiratory Protection:	If exposure limits are exceeded, an approved particulate respirator, or supplied air respirator, appropriate for the airborne concentrations, should be used. Selection and use of the respiratory protective equipment must be in accordance with applicable regulations and

An emergency eye wash fountain and shower are recommended.

good industrial hygiene practices.

#### 9. Physical & Chemical Properties

Other:

Appearance:	White or grayish white material
Odor:	Odorless
Odor threshold:	Not Applicable
pH at 25 degrees C:	12.45
Melting Point:	4658 °F (2570 °C)
Boiling Point and range:	5162 °F (2850 °C)
Flash Point:	Not Applicable
Evaporation Rate:	Not Applicable
Flammability:	Not Applicable
Upper/lower flammability or explosiv	e limits Not Applicable
Vapor pressure/density:	Non Volatile
Relative density:	2.0-2.8
Solubility:	Neglible in water but reacts with water to form calcium hydroxide and magnesium hydroxide. Soluble in acids, glycerin, and sugar solutions
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature:	Not Available
Decomposition temperature:	Not available
Viscosity:	Not Applicable



## **Deadburnt Dolomite**

Revision date: July 11, 2019

Reactivity:	Reacts with water to form calcium hydroxide and magnesium hydroxide, releasing heat. Reacts with acids to form calcium sal releasing heat. Reacts with carbon dioxide in air to form calciur carbonate. See also Incompatibility below.
Chemical stability:	Stable under normal storage and handling conditions.
Possibility of Hazardous Reactions:	See "reactivity" above.
Conditions to avoid:	Vicinity of incompatible materials.
Incompatibility:	This product should not be mixed or stored with the following materials, due to the potential for violent reaction and release of heat: • water (unless in a controlled process) • acids • reactive fluoridated compounds • reactive brominated compounds • reactive powdered metals • reactive phosphorous compounds • aluminum powder • organic acid anhydrides • nitro-organic compounds • interhalogenated compounds

Hazardous decomposition products: None

#### **11. Toxicological Information**

Likely routes of exposure & symptoms:		
Eyes:	Contact can cause severe irritation or burning of eyes, including permanent damage.	
Skin:	Contact can cause severe irritation or burning of skin, especially in the presence of moisture.	
Ingestion:	This product can cause severe irritation or burning of gastrointestinal tract if swallowed.	
Inhalation:	This product can cause severe irritation of the respiratory system.	



**Deadburnt Dolomite** 

Revision date: July 11, 2019

Chronic health effects:	This product contains trace amounts of crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica can cause silicosis, as serious lung disease.
Respiratory or skin sensitization:	This material is not known to cause sensitization
Germ cell mutagenicity:	No data available.
Carcinogenicity:	This product is not listed as carcinogenic by OSHA, IARC, NTP, ACGIH, or the EU Directives. This product may contain trace amounts of crystalline silica quartz which is listed by IARC as "Carcinogenic to Humans" (Group 1) and "Known to be a Human Carcinogen" by NTP (National Toxicology Program).
Reproductive toxicity:	No Data Available.
Numerical Measures of Toxicity	Crystalline Silica: Oral Rate LD <sub>50</sub> > 22,500 mg/kg

#### 12. Ecological Information

Because of the elevated pH of this product, it might be expected to produce some ecotoxicity upon exposure to certain aquatic organisms and aquatic systems in high concentrations This material shows no bioaccumulation effect or food chain concentration toxicity.

#### **13.** Disposal Considerations

Dispose of contents in accordance with federal, state, provincial and local regulations.

#### 14. Transport Information

UN Number	UN1910			
UN Proper shipping name	Calcium Oxide			
Transport Hazard class(es)	When transported by air only: Hazard Class 8-Corrosive			
Packing group	When transported by air only: Packing Group III			
Environmental hazards	This material is alkaline and if released into water or moist soil will cause an increase in pH			
Transport in bulk (according to Annex II of MARPOL 73/79 and the IBC				
Code:				



# **Deadburnt Dolomite**

Revision date: July 11, 2019

Special precautions which a user needs to be aware of When being transported by air, quicklime is classified in the Department of Transportation (DOT) regulations as a hazardous material. (49 CFR 172.101). For aircraft transport only, Calcium Oxide is classified as Hazard Class 8-Corrosive, UN1910, Packing Group III. For passenger aircraft, the maximum net quantity allowed per container is 25 kg. For cargo aircraft, the maximum net quantity allowed per container is 100 kg. For quantities greater than 25 kg up to and including 100 kg, the container shall be labeled with CARGO AIRCRAFT ONLY. Because express carriers (i.e., Federal Express, Airborne Express, and United Parcel Service) ship by air, quicklime presented to these carriers for shipment must be packaged, marked, and labeled in accordance with IATA requirements, and must be accompanied by the appropriate shipping documentation. Only personnel trained and certified under applicable DOT Hazardous Materials Regulations (contained in Title 49 of the Code of Federal Regulations) may prepare any quicklime product for air transport. Quicklime is not classified as a hazardous material by DOT when transported by means other than by air.

#### 15. Regulatory Information

Regulatory information					
CERCLA Hazardous Substances		Not listed			
SARA Toxic Chemical (40 CFR 372.65)	Not listed				
SARA Section 302 Extremely Hazardous	Not listed				
SARA 311/312	Not listed				
SARA Section 313 Toxic Chemicals repo	None				
Threshold planning quantity (TPQ)	Not listed				
RCRA Hazardous Waste Classification (	Not Classified				
EPA Toxic Substances Control Act (TSCA) Status	The components of this product are each listed on the TSCA Inventory List in the "active" status.				
California Proposition 65	Airborne crystalline silica particulates of respirable size are known to the State of California to cause cancer.				
NFPA ratings	Health: 3 Fire: 0 Reactivity: 0 🛛 ₩				
HMIS Ratings	Health: 3 Fire: 0 Reactivity: 1 Perso	nal protection: E			
OSHA Specifically regulated substance	Not listed				
OSHA Air contaminant (29 CFR 1910.10	Listed				
MSHA	Not listed				
Canada DSL	Listed				
Canadian WHMIS Classification	D2A, Materials Causing other toxic effects.				
	E, Corrosive Material				



### **Deadburnt Dolomite**

Revision date: July 11, 2019

**Canada CPR** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation of a Canada and this SDS contains all the required information.

16. Other l	Information					
List	of GHS	H315: Causes skin irritation				
Haza	ard	H318: Causes serious eye damage				
State	ements:	H335: May cause respiratory irritation.				
		H350: May cause cancer through inhalation				
		H372: Causes damage to lungs	through p	prolonged or repeated exposure by inhalation.		
List	of GHS	P201: Obtain special instructio	ons before	use.		
Prec	<b>Precautionary</b> P202: Do not handle until all safety precautions have been read and understood.					
State	ements:	P233: Keep container tightly closed				
	P260: Do not breathe dust.					
		P264: Wash thoroughly after handling.				
		P270: Do not eat, drink or smo	70: Do not eat, drink or smoke when using this product.			
		P271: Use only outdoors or in well-ventilated area				
P280: Wear protective gloves, clothing and eye protection			nd eye protection			
۵bb	reviations					
CER		hensive Environmental	RCRA	Resource Conservation and Recovery Act		
		se, Compensation and Liability	-			
	Act					
SARA		nd Amendments and	IARC	International Agency for Research on Cancer		
	•	prization Act				
NTP		Il Toxicology Program				
		-07 -0 -				

The information contained herein is believed to be accurate and reliable as of the date hereof. However, Carmeuse makes no representation, warranty or guarantee as to results or as to the information's accuracy, reliability or completeness. Carmeuse has no liability for any loss or damage that may result from use of the information. Each user is responsible to review this information, satisfy itself as to the information's suitability and completeness, and circulate the information to its employees, customers and other appropriate third parties.