

1. Identification

Product Name: Oil Coated Fusite

Synonyms: None

Recommended Uses: Water treatment, steel flux, caustic agent, pH adjustment, acid gas absorption, construction

Manufacturer: Carmeuse Americas

US Office
11 Stanwix Street, 21st Floor
Pittsburgh, PA 15222
Phone: (412) 995-5500
Fax: (412) 995-5594

Canadian Office
PO Box 190
Ingersoll, ON N5C 3K5
Phone: (519) 423-6283
Fax: (519) 423-6545

Emergency Contact: Infotrac: (800) 535-5053 (24 hrs a day, 7 days a week)

2. Hazards Identification

GHS classification	Physical Hazards	
	Combustible Liquid (<i>refers to coating on pebble</i>)	Category 4
GHS Label Elements:	Health Hazards	
	Skin Irritation	Category 2
	Eye Damage	Category 1
	Carcinogenicity	Category 1A
	Specific Target Organ Toxicity – Single Exposure	Category 3
	Specific Target Organ Toxicity – Repeated Exposure	Category 1
	Signal Word:	Danger
Hazard Statements:	Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause cancer through inhalation Causes damage to lungs through prolonged or repeated exposure by inhalation. Combustible liquid (<i>refers to coating on pebbles</i>)	
Precautionary Statements:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in well-ventilated area Wear protective gloves, clothing and eye protection Do not use water on material spills. Keep away from flames and hot surfaces Store in a well-ventilated place. Keep cool	

Safety Data Sheet Oil Coated Fusite

Revision date:
 July 11, 2019

Pictograms:



3. Composition

<u>Chemical name</u>	<u>% by weight</u>	<u>CAS#</u>
Calcium oxide	> 55	1305-78-8
Magnesium oxide	< 34	1309-48-4
Iron Oxide	< 12	1309-37-1
Clarified Petroleum oils	< 2	64741-62-4
Silica-crystalline quartz	0.1 - 2	14808-60-7

4. First Aid Measures

Eyes:	Immediately flush eyes with generous amounts of water for at least 15 minutes. Pull back the eyelid to ensure that all lime dust has been washed out. Seek medical attention immediately. Do not rub eyes.
Skin:	Wash exposed area with large amounts of water. Seek medical attention immediately.
Ingestion:	Do not induce vomiting. Seek medical attention immediately. Never give anything by mouth unless instructed to do so by medical personnel.
Inhalation:	Move victim to fresh air. Seek medical attention if necessary. If breathing has stopped, give artificial respiration
Most Important Symptoms:	Irritation of skin, eyes, gastrointestinal tract or respiratory tract.
Immediate medical attention / special treatment?	See first aid information above. Note to Physicians: Provide general supportive measures and treat symptomatically.

5. Fire Fighting Measures

Suitable (and unsuitable) fire extinguishing media:	Use dry chemical fire extinguisher. Do not use water or halogenated compounds, except that large amounts of water may be used to deluge small quantities of this product.
Specific hazards arising from the product	Inhalation, skin or eye contact, can result in serious injury. The oil coating is combustible. This product reacts with water, and can release heat sufficient to ignite combustible materials. This product is not considered to be an explosion hazard, although reaction with water or other incompatible materials may rupture containers. When this product is wet, it can be very slippery and can result in a slip hazard. Hazardous Combustion Products: None.

Oil Coated Fusite

Revision date:
July 11, 2019

Special protective equipment and precautions for fire fighters

Wear full fire-fighting turn-out gear (full Bunker gear), and respiratory protection (SCBA) to prevent inhalation, skin or eye contact.

6. Accidental Release Measures

Personal precautions, protective equipment, emergency procedures:

Avoid inhalation, eye and skin contact. Avoid generating airborne dust. Wear appropriate protective clothing as described in section 8.

Methods and materials for containment and clean up:

Utilize cleanup methods that minimize generating dust: vacuum. Avoid dry sweeping. Do not use water on large spills, as this product reacts with water and releases heat. Residue on surfaces may be removed with copious amount of water or vinegar.

7. Handling & Storage

Safe Handling: Avoid inhalation, skin and eye contact. Avoid generating airborne dust. An eye wash station should be readily available when this product is handled.

Safe Storage: Keep in tightly closed containers. Protect containers from physical damage. Store in a cool, dry, and well-ventilated location. Do not store near incompatible materials (see Section 10 below). Keep away from moisture. Long-term storage in aluminum containers is not recommended, as calcium oxide may corrode aluminum over long periods of time

8. Exposure Controls/Personal Protection

Occupational Exposure Limits

	OSHA PEL (mg/m ³)	ACGIH TLV (mg/m ³)	Ont. Reg. 833 TWA EV (mg/m ³)
Calcium oxide	5	2	2
Magnesium oxide	15	10	10
Iron Oxide*	5 (fume) 15 (total) 5 (respirable)	5	5 (respirable)
Clarified Petroleum oils	-	-	-
Silica, <i>crystalline quartz, cristobalite and tridymite</i>	0.05 (respirable)	0.025 (respirable)	0.1

*PELs for Particulates Not Otherwise Classified

Engineering Controls: Use with adequate general or local exhaust ventilation and to maintain exposure below occupational exposure limits.

Individual Protection Measures (Personal Protective Equipment):

Oil Coated Fusite

Revision date:
July 11, 2019

Specific Eye / Face Protection:

Safety glasses with side shields. In windy conditions, or if work activity generates elevated airborne dust levels, dust proof or chemical goggles are recommended. Contact lenses should not be worn.

Specific Skin Protection:

When there is a risk of skin contact, wear appropriate clothing and gloves to prevent contact.

Specific Respiratory Protection:

If exposure limits are exceeded, an approved particulate respirator, or supplied air respirator, appropriate for the airborne concentrations, should be used. Selection and use of the respiratory protective equipment must be in accordance with applicable regulations and good industrial hygiene practices.

Other:

An emergency eye wash fountain and shower are recommended.

9. Physical & Chemical Properties

Appearance:	White or grayish white material
Odor:	Odorless
Odor threshold:	Not Applicable
pH at 25 degrees C:	12.45
Melting Point:	4658 °F (2570 °C)
Boiling Point and range:	5162 °F (2850 °C)
Flash Point:	140 °F min. (oil coating)
Evaporation Rate:	Not Applicable
Flammability:	Not Applicable
Upper/lower flammability or explosive limits	Not Applicable
Vapor pressure/density:	Non Volatile
Relative density:	2.0-2.8
Solubility:	Negligible in water but reacts with water to produce Ca(OH)_2 and heat Soluble in acids, glycerin, and sugar solutions
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature:	Not Available
Decomposition temperature:	Not available
Viscosity:	Not Applicable

10. Stability & Reactivity

Reactivity:	Reacts with water to form calcium hydroxide and magnesium hydroxide, releasing heat. Reacts with acids to form calcium salts, releasing heat. Reacts with carbon dioxide in air to form calcium carbonate. See also Incompatibility below.
Chemical stability:	Stable under normal storage and handling conditions.
Possibility of Hazardous Reactions:	See "reactivity" above.
Conditions to avoid:	Vicinity of incompatible materials.
Incompatibility:	<p>This product should not be mixed or stored with the following materials, due to the potential for violent reaction and release of heat:</p> <ul style="list-style-type: none">• water (unless in a controlled process)• acids• reactive fluoridated compounds• reactive brominated compounds• reactive powdered metals• reactive phosphorous compounds• aluminum powder• organic acid anhydrides• nitro-organic compounds• interhalogenated compounds
Hazardous decomposition products:	None

11. Toxicological Information

Likely routes of exposure & symptoms:

Eyes:	Contact can cause severe irritation or burning of eyes, including permanent damage.
Skin:	Contact can cause severe irritation or burning of skin, especially in the presence of moisture.
Ingestion:	This product can cause severe irritation or burning of gastrointestinal tract if swallowed.
Inhalation:	This product can cause severe irritation of the respiratory system.

Oil Coated Fusite

Revision date:
July 11, 2019

Chronic health effects:	This product contains trace amounts of crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica can cause silicosis, a serious lung disease.
Respiratory or skin sensitization:	This material is not known to cause sensitization
Germ cell mutagenicity:	No data available.
Carcinogenicity:	This product is not listed as carcinogenic by OSHA, IARC, NTP, ACGIH, or the EU Directives. This product may contain trace amounts of crystalline silica quartz which is listed by IARC as "Carcinogenic to Humans" (Group 1) and "Known to be a Human Carcinogen" by NTP.
Reproductive toxicity:	No Data Available.
Numerical Measures of Toxicity	Crystalline Silica: Oral Rate LD ₅₀ > 22,500 mg/kg

12. Ecological Information

Because of the elevated pH of this product, it might be expected to produce some ecotoxicity upon exposure to certain aquatic organisms and aquatic systems in high concentrations
This material shows no bioaccumulation effect or food chain concentration toxicity.

13. Disposal Considerations

Dispose of contents in accordance with federal, state, provincial and local regulations.

14. Transport Information

UN Number	UN1910
UN Proper shipping name	Calcium Oxide
Transport Hazard class(es)	When transported by air only: Hazard Class 8-Corrosive
Packing group	When transported by air only: Packing Group III
Environmental hazards	This material is alkaline and if released into water or moist soil will cause an increase in pH
Transport in bulk (according to Annex II of MARPOL 73/79 and the IBC Code:	

Oil Coated Fusite

Revision date:
July 11, 2019

**Special precautions
which a user needs to
be aware of**

When being transported by air, quicklime is classified in the Department of Transportation (DOT) regulations as a hazardous material. (49 CFR 172.101). For aircraft transport only, Calcium Oxide is classified as Hazard Class 8-Corrosive, UN1910, Packing Group III. For passenger aircraft, the maximum net quantity allowed per container is 25 kg. For cargo aircraft, the maximum net quantity allowed per container is 100 kg. For quantities greater than 25 kg up to and including 100 kg, the container shall be labeled with CARGO AIRCRAFT ONLY. Because express carriers (i.e., Federal Express, Airborne Express, and United Parcel Service) ship by air, quicklime presented to these carriers for shipment must be packaged, marked, and labeled in accordance with IATA requirements, and must be accompanied by the appropriate shipping documentation. Only personnel trained and certified under applicable DOT Hazardous Materials Regulations (contained in Title 49 of the Code of Federal Regulations) may prepare any quicklime product for air transport. Quicklime is not classified as a hazardous material by DOT when transported by means other than by air.

15. Regulatory Information

CERCLA Hazardous Substances	Not listed
SARA Toxic Chemical (40 CFR 372.65)	Not listed
SARA Section 302 Extremely Hazardous Substances (40 CFR 355)	Not listed
SARA 311/312	Not listed
SARA Section 313 Toxic Chemicals reporting requirements	None
Threshold planning quantity (TPQ)	Not listed
RCRA Hazardous Waste Classification (40 CFR 261)	Not Classified
EPA Toxic Substances Control Act (TSCA) Status	The components of this product are each listed on the TSCA Inventory List in the "active" status.
California Proposition 65	Airborne crystalline silica particulates of respirable size are known to the State of California to cause cancer.
NFPA ratings	Health: 3 Fire: 2* Reactivity: 0 W
HMIS Ratings	Health: 3 Fire: 2* Reactivity: 1 Personal protection: E *2 rating is due to oil component of material
OSHA Specifically regulated substance (29 CFR 1910)	Not listed
OSHA Air contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A)	Listed
MSHA	Not listed
Canada DSL	Listed
Canadian WHMIS Classification	D2A, Materials Causing other toxic effects. E, Corrosive Material B, Combustible Material (<i>oil coating</i>)



Canada CPR This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation of a Canada and this SDS contains all the required information.

16. Other Information

List of GHS	H227: Combustible liquid (<i>coating on pebbles</i>)
Hazard	H315: Causes skin irritation
Statements:	H318: Causes serious eye damage H335: May cause respiratory irritation. H350: May cause cancer through inhalation H372: Causes damage to lungs through prolonged or repeated exposure by inhalation.
List of GHS	P201: Obtain special instructions before use.
Precautionary	P202: Do not handle until all safety precautions have been read and understood.
Statements:	P210: Keep away from flames and hot surfaces P233: Keep container tightly closed P260: Do not breathe dust. P264: Wash thoroughly after handling. P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in well-ventilated area P280: Wear protective gloves, clothing and eye protection P403+P235: Store in a well-ventilated place. Keep cool

Abbreviations

CERCLA	Comprehensive Environmental Response, Compensation and Liability Act	RCRA	Resource Conservation and Recovery Act
SARA	Superfund Amendments and Reauthorization Act	IARC	International Agency for Research on Cancer
NTP	National Toxicology Program		

The information contained herein is believed to be accurate and reliable as of the date hereof. However, Carmeuse makes no representation, warranty or guarantee as to results or as to the information's accuracy, reliability or completeness. Carmeuse has no liability for any loss or damage that may result from use of the information. Each user is responsible to review this information, satisfy itself as to the information's suitability and completeness, and circulate the information to its employees, customers and other appropriate third parties.