



Name of the product
Dolomitic Quicklime

Revision Date: March 2024 Version: 2.0/EN

```
SECTION 1: Identification
```

#### 1.1. Product identifier

Trade name

Blended Quicklime

#### Other names / Synonyms

Dolime, Dolo Fines, Dolopel<sup>®</sup>, Hi Mag/Dolo Quicklime 12%MgO Blend, InjectolimeTM, Mini Pebble, Pebble Lime, Pebble Lime-Large, Pebble Lime-Rescreened, Pebble Lime-Small, Pulverized Lime, Dolo Quicklime Fines, Dolomitic Injectolime<sup>®</sup>, Dolomitic Quicklime, Granular Dolime

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses of the substance or mixture

Ca-Mg hydroxide manufacturing, fiberglass production, BOF and EAF stellmaking, caustic agent, pH adjustment, acid gas absorption, construction, used in production of refractory brick. Restricted to professional users.

Uses advised against

#### None known.

1.3. Details of the supplier of the safety data sheet

#### Company and address

**Carmeuse Americas CA** 

PO Box 190 ON N5C 3K5 Ingersoll Canada Phone: (519) 423-6283 Fax: (519) 423-6545 https://www.carmeuse.com/na-en

#### Contact person

Carmeuse Americas Website: https://www.carmeuse.com/na-en

#### E-mail

jason.ruckman@carmeuse.com

#### 1.4. Emergency telephone number

Infotrac: (800) 535-5053 (24hr/7days a week) See also section 4 "First aid measures".

SECTION 2: Hazard(s) identification

Classified according to WHMIS 2022.

#### 2.1. ▼Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Eye Dam. 1; H318, Causes serious eye damage.

STOT SE 3; H335, May cause respiratory irritation.

Carc. 1A; H350i, May cause cancer by inhalation.

STOT RE 1; H372, Causes damage to organs through prolonged or repeated exposure.

#### 2.2. Label elements

Hazard pictogram(s)



Danger

Conforms to Hazardous Products Regulations (SOR/2022-272)



Name of the product

### **Dolomitic Quicklime**

Revision Date: March 2024 Version: 2.0/EN

#### Hazard statement(s)

Causes skin irritation. (H315) Causes serious eye damage. (H318) May cause respiratory irritation. (H335) May cause cancer by inhalation. (H350i) Causes damage to organs through prolonged or repeated exposure. (H372)

#### Precautionary statement(s)

General

#### ▼ Prevention

Obtain special instructions before use. (P201) Do not breathe dust. (P260) Wash hands and exposed skin thoroughly after handling. (P264) Wear eye protection/protective gloves. (P280)

#### ▼Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338) IF exposed or concerned: Get medical advice/attention. (P308+P313)

Immediately call a POISON CENTER/doctor. (P310)

Get medical advice/attention if you feel unwell. (P314)

#### Storage

Store in a well-ventilated place. Keep container tightly closed. (P403+P233)

Disposal

Dispose of contents/container in accordance with local regulation (P501)

#### Hazardous substances

Calcium oxide

- Magnesium oxide
- Silica-crystalline quartz

#### Additional labelling

Restricted to professional users.

#### 2.3. Other hazards

#### Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

SECTION 3: Composition/Information on Ingredients

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. ▼Mixtures

Product/substance	Identifiers	% <b>w/w</b>	Classification	Note
Calcium oxide	CAS No.: 1305-78-8	>55%	Skin Irrit. 2, H315	
			Eye Dam. 1, H318	
			STOT SE 3, H335	
Magnesium oxide	CAS No.: 1309-48-4	>21%	Skin Irrit. 2, H315	
			Eye Irrit. 2, H319	
			STOT SE 3, H335	
Silica-crystalline quartz	CAS No.: 14808-60-7	0.1-2%	Carc. 1A, H350i	
			STOT RE 1, H372	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available. Other information

Crystalline Silica is reported as total silica and not just the respirable fraction. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Conforms to Hazardous Products Regulations (SOR/2022-272)



Revision Date: March 2024 Version: 2.0/EN

#### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

#### General information

**MFUSE** 

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

#### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

#### Burns

#### Not applicable.

#### 4.2. Most important symptoms and effects, both acute and delayed

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

#### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

#### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are

produced. These are: Some metal oxides

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact a poison centre in order to obtain further advice. See section 1 "Emergency telephone number".





Name of the product

### **Dolomitic Quicklime**

Revision Date: March 2024 Version: 2.0/EN

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.
6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up Limit spillage, sweep up and shovel into appropriate containers for disposal. Store in suitable, closed containers for disposal.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Avoid direct contact with the product. Avoid contact during pregnancy and while nursing. Smoking, drinking and consumption of food is not allowed in the work area. See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

No special conditions required.

Recommended storage material Always store in containers of the same material as the original container.

#### Storage temperature

#### No specific requirements

Incompatible materials

Water Strong acids reactive fluoridated compounds reactive brominated compounds reactive powdered metals Organic acid anhydrides interhalogen compounds aluminum powder reactive phosphorous compounds

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

#### 8.1. ▼Control parameters ALBERTA

Calcium oxide Long term exposure limit (8 hours) (mg/m³): 2 Annotations:



### <u>tts</u> CARMEUSE

## Name of the product Dolomitic Quicklime

Revision Date: March 2024 Version: 2.0/EN

3 = Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.

Magnesium oxide Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 10

Silica-crystalline quartz Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 0.025 Annotations: A2 = Silica-crystalline quartz is a suspected human carcinogen.

Occupational Health and Safety Code 2009 Order, Alta Reg 87/2009 (revised in 2018)

BRITISH COLUMBIA Calcium oxide Time-Weighted Average Limit (TWA): 2 mg/m<sup>3</sup>

Magnesium oxide Time-Weighted Average Limit (TWA): 10 mg/m<sup>3</sup> (inhalable) ; 3 mg/m<sup>3</sup> (respirable) Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 10 mg/m<sup>3</sup> (respirable)

Silica-crystalline quartz Time-Weighted Average Limit (TWA): 0.025 mg/m³

OHS Regulation Part 5: Chemical Agents and Biological Agents.

ONTARIO Calcium oxide Time-Weighted Average Limit (TWA): 2 mg/m<sup>3</sup>

Magnesium oxide Time-Weighted Average Limit (TWA): 10 mg/m<sup>3</sup> Annotations: (I) = Inhalable fraction.

Silica-crystalline quartz Time-Weighted Average Limit (TWA): 0.10 mg/m<sup>3</sup> Annotations: (R) = Respirable fraction.

Regulation 833 (Control of Exposure to Biological or Chemical Agents) and Ontario Regulation 490/09 (Designated Substances)

QUEBEC Calcium oxide Long term exposure limit (8 hours) (mg/m³): 2

Magnesium oxide Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 10 Annotations: Id = Inhalable dust.

Silica-crystalline quartz Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 0.1 Annotations: EM = Exposure must be reduced to a minimum in accordance with section 42. Rd = Respirable dust.

Regulation respecting occupational health and safety (Chapter S-2.1, r. 13)

Conforms to Hazardous Products Regulations (SOR/2022-272)

### <u>tts</u> CARMEUSE

## Name of the product Dolomitic Quicklime

Revision Date: March 2024 Version: 2.0/EN

#### SASKATCHEWAN

Calcium oxide Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 2 Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 4

Magnesium oxide Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 10 Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 20

Silica-crystalline quartz

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 0.05

Annotations:

T20 = Substance is also included in Table 20 of The Occupational Health and Safety Regulations and subject to Sections 306 and 311

The Occupational Health and Safety Regulations, 2020, Chapter S15.1 Reg 10.

#### 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

#### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

#### Exposure scenarios

There are no exposure scenarios implemented for this product.

#### **Exposure limits**

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

#### Appropriate technical measures

Do not recirculate outlet air that contain the substances.

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and showers are clearly marked.

Ensure that eyewash stations and safety showers are located within easy reach.

#### Hygiene measures

Take off contaminated clothing and wash it before reuse.

#### Measures to avoid environmental exposure

· All ventilation systems should be filtered before discharge to atmosphere.

· Avoid releasing to the environment.

· Contain the spillage. Any large spillage into watercourses must be alerted to the regulatory authority.

#### Individual protection measures, such as personal protective equipment

#### Generally

Appropriate footwear, additional skin & eye protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Respiratory Equipment**

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear an appropriate NIOSH approved respirator if concentration levels exceed the safe exposure limits.

#### Skin protection

Since calcium oxide is classified as irritating to skin, dermal exposure has to be minimised as far as technically feasible. Protective standard working clothes fully covering skin, full length trousers, long sleeved overalls, with close fittings at openings and shoes resistant to caustics and avoiding dust penetration are required to be worn.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. Considering the parameters specified by the glove



# CARMEUSE

## Name of the product Dolomitic Quicklime

Revision Date: March 2024 Version: 2.0/EN

manufacturer. The time to breakthrough for any glove material may be different per glove manufacturer. In the case of mixtures, the

protection time of the gloves cannot be accurately estimated.

#### Eye protection

Do not wear contact lenses. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn: chemical splash goggles and/

or face shield.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

```
Physical state
      Solid
   Colour
      White to dark Gray
   Odour
      None
   Odour threshold (ppm)
      Not applicable
  рΗ
   pH in solution
      12.5 at 25°C (%)
   Density (g/cm<sup>3</sup>)
      3.2-3.4
   Kinematic viscosity
      Not applicable
      Particle size: Variable
Phase changes
   Melting point (°C)
      2570
   Boiling point (°C)
      5162
   Vapour pressure
      Not applicable
   Relative vapour density
      Not applicable
   Decomposition temperature (°C)
      Not applicable
   Evaporation rate (n-butylacetate = 100)
      Not applicable
Data on fire and explosion hazards
   Flash point (°C)
      Not applicable
   Flammability (°C)
      Not applicable
   Auto-ignition temperature (°C)
      Not applicable
   Explosion limits (\% v/v)
      Not applicable
Solubility
   Solubility in water
      1.3376 g/l at 20 °C (68 °F)
      Test method: Regulation (EC) No. 440/2008, Annex, A.6
```



## Name of the product **Dolomitic Quicklime**

Revision Date: March 2024 Version: 2.0/EN

n-octanol/water coefficient (LogKow) Testing not relevant or not possible due to the nature of the product. Solubility in fat (g/L) Testing not relevant or not possible due to the nature of the product. 9.2. Other information Sensitivity to shock No Evaporation rate (n-butylacetate = 100) Not applicable Other physical and chemical parameters No data available. Oxidizing properties Not applicable SECTION 10: Stability and reactivity 10.1. Reactivity No data available. 10.2. Chemical stability The product is stable under the conditions, noted in section 7 "Handling and storage". 10.3. Possibility of hazardous reactions None known. 10.4. Conditions to avoid

#### 10.4. Conditions to avoid None known.

MFUSF

#### 10.5. Incompatible materials

Water Strong acids reactive fluoridated compounds reactive brominated compounds reactive powdered metals Organic acid anhydrides interhalogen compounds aluminum powder reactive phosphorous compounds

#### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

LD50

22500 mg/kg

#### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

▼ Acute toxicity Product/substance Species: Route of exposure: Test: Result:	Calcium oxide Rat Oral LD50 3059 mg/kg	
Product/substance Species: Route of exposure:	Silica-crystalline quartz Rat Oral	

#### Skin corrosion/irritation

Causes skin irritation.

Test: Result:

Conforms to Hazardous Products Regulations (SOR/2022-272)



## Name of the product Dolomitic Quicklime

Revision Date: March 2024 Version: 2.0/EN

#### Serious eye damage/irritation

Causes serious eye damage.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

May cause cancer by inhalation.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation.

#### ▼STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion. The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

#### ▼Other information

Silica-crystalline quartz has been classified by IARC as a group 1 carcinogen.

#### SECTION 12: Ecological information

#### 12.1. Toxicity

#### No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

#### 12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

#### Waste treatment methods

None of the components are listed

#### Specific labelling

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information



## Name of the product Dolomitic Quicklime

CARMEUSE

Revision Date: March 2024 Version: 2.0/EN

UI	N/ID U	N proper shipping name	Hazard class(es)	PG*	14.11 Env**	4.214.314.414.50the information:
TDG	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
ATA	-	-	-	-	-	-
Packing	group					
Additio	nal info	l hazards ormation ous goods according to	TDG, IATA and IMDG.			
Not a 14.7. Tr	applica	t in bulk according to A	nnex II of Marpol and the IBC Code			
SECTIC	DN 15:F	Regulatory information				
15.2. Ca DSL, Ca M Si 15.4. Re Restr Peop Prega preca 15.5. De No s Addition Not a 15.7. Ch No Sources	anadian / NDSL alcium of lagnesi ilica-cry estrictic ricted to ricted to ricted to ricted to ricted to ricted to ricted to ric	lists oxide is listed um oxide is listed stalline quartz is listed ons for application o professional users. or the age of 18 shall no omen and women breas or design of the workp for specific education requirements. rmation	l regulations/legislation specific for the subst t be exposed to this product. tfeeding must not be exposed to this produc place needed to eliminate exposure, must be	t. The risk, ar	nd poss	sible technical
SECTIC	ON 16: 0	Other information				
H315 H318 H319 H350 H350 H372 The full None Abbrevi ANSI ATE = BCF = CAS =	5, Caus 8, Caus 9, Caus 5, May c 2, Caus text of e known ations a = Ame = Acute = Bioco = Chem	identified uses as ment	e. n. ion. ion. rough prolonged or repeated exposure. ioned in section 1			
Dolomitic						

Conforms to Hazardous Products Regulations (SOR/2022-272)



### **Dolomitic Quicklime**

Revision Date: March 2024 Version: 2.0/EN

GHS = Globally Harmonized System of Classification and Labelling of Chemicals HHNOC = Health Hazards Not Otherwise Classified IARC = International Agency for Research on Cancer IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) NDSL = Non-domestic substances list OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PHNOC = Physical Hazards Not Otherwise Classified RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail SCL = A specific concentration limit. SOR = Statutory Orders and Regulations STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TDG = Transportation of Dangerous Goods

TWA = Time weighted average

UN = United Nations

MFUSE

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

WHIMS = Workplace Hazardous Materials Information System

#### Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by WHMIS 2022

#### **▼**Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

#### Country-language: CA-en

Disclaimer: The information contained herein is believed to be accurate and reliable as of the date hereof. However, Carmeuse makes no representation, warranty or guarantee as to results or as to the information's accuracy, reliability or completeness. Carmeuse has no liability for any loss or damage that may result from use of the information. Each user is responsible to review this information, satisfy itself as to the information's suitability and completeness, and circulate the information to its employees, customers and other appropriate third parties.